

制造品种一览表 LIST OF PRODUCTS

◆ 小型铝电解电容器 MINIATURE ALUMINIUM ELECTROLYTIC CAPACITORS

用途区分 Classification	系列 Series	JIS Configuration	概要 Applications	温度范围 Operating Temperature (°C)	特性 Features				额定电压范围 Rated W. V (V. DC)	额定静电容量范围 Capacitance (μF)	页码 Page
					标准品 Standard type	小型化品 Smaller-sized&low	低阻抗品 Low impedance	长寿命品 Long life			
贴片品V-Chip	RVT	Chip	贴片型105°C标准品 Chip Type ,Wide Temperature Range	-55~+105°C	●	●		●	6.3~100	0.47~1500	19
	RVH	Chip	贴片型125°C长寿命品 Chip Type ,Wide Temperature Range	-55~+125°C		●		●	10~50	10~330	20
	RVN	Chip	贴片型无极性品 Chip Type , Non-Polarized	-55~+105°C	●	●			6.3~50	0.1~100	21
	RVK	Chip	贴片型低漏电流品 Chip Type , Low Leakage Current	-55~+105°C	●	●			6.3~50	0.1~330	22
	NEW RYK	Chip	贴片型高压品 Chip Type ,High Voltage	-40~+105°C	●	●			200~400	1~15	23
标准品 General Purpose	MP	04	85°C标准品 Standard, For General Purposes	-40(-25)~+85°C	●				6.3~450	0.47~33000	25
	HM	04	105°C标准品 Wide Temperature Range	-40(-25)~+105°C	●				6.3~450	0.1~33000	27
开关电源用 For Switching Power Supply	YK	04	105°C开关电源专用品 For Switching Power Supply	-40(-25)~+105°C		●	●		200~500	1~470	29
	FM	04	105°C长寿命开关电源、LED驱动器专用品 Long Life For Switching Power Supply and LED Drive	-40(-25)~+105°C		●	●	●	6.3~450	1~6800	32
	PZ	04	105°C高压、小型化、大纹波品 High Voltage , Smaller-sized\High Ripple Current	-40(-25)~+105°C		●	●		200~450	18~390	35
	PB	04	105°C小型化、大纹波品 High Voltage , Smaller-sized\High Ripple Current	-40(-25)~+105°C		●	●	●	35~450	12~1500	37
	NEW SXW	04	105°C过电压对策规格品 Over-Voltage Venting Specification	-40(-25)~+105°C		●	●		200~400	4.7~330	41
	AX	04	105°C用于便携式AC适配器的超小型品 Ultra Miniaturized for AC-adaptor of portable device	-40~+105°C		●	●		6.3~10/400	4.7~1200	43
高频低阻抗品 Low Impedance	FA	04	高频低电阻标准品 Low Impedance	-40~+105°C		●	●		6.3~100	1~10000	45
	FL	04	高频超低电阻品 Extremely Low Impedance	-40~+105°C		●	●		6.3~50	27~8200	49
	FLK	04	超高纹波电流、低电阻品 Ultra High Ripple Current, Low Impedance	-40~+105°C		●	●		10~35	220~1800	51
	FD	04	高频超低电阻、高可靠性品 Low Impedance, High Reliability	-40~+105°C			●	●	6.3~100	22~12000	52
	FK	04	高频低电阻、高可靠性品 Low Impedance, High Reliability	-40~+105°C			●	●	6.3~100	22~10000	55
	NEW FT	04	125°C1000~4000小时高频低电阻品 125°C1000~4000Hours, Low Impedance	-40~+125°C			●	●	10~35	22~2200	58
长寿命品 Long Life	HT	04	105°C5000小时高压、高可靠性品 High Voltage Low Impedance, High Reliability	-40(-25)~+105°C		●	●	●	160~500	1.0~330	60
	RB	04	105°C8000~10000小时高压、低电阻、高可靠性品 High Voltage Low Impedance, High Reliability	-40(-25)~+105°C		●	●	●	160~450	1.0~330	63
	NEW LLE	04	105°C10000~15000小时高压、高可靠性品 High Voltage Low Impedance, High Reliability	-40(-25)~+105°C		●	●	●	160~450	1.0~68	66
	NEW LLX	04	125°C3000~5000小时高压、高可靠性品 High Voltage Low Impedance, High Reliability	-40(-25)~+125°C		●	●	●	160~400	1.0~27	68
高温对应品 High Temperature	HA	04	125°C5000小时高压、高可靠性品 High Temperature Range For +125°C, High Reliability	-40(-25)~+125°C		●	●	●	200~450	1~220	70
	HW	04	130°C高压、高可靠性品 High Temperature Range For +130°C, High Reliability	-40(-25)~+130°C		●	●	●	200~450	1~220	72
	NEW BT	04	125°C4000小时品, 车载专用 +125°C4000Hours, for Automotive	-40(-25)~+125°C		●	●	●	10~450	2.2~4700	74
特殊品 Special type	FHX	04	闪光灯专用 For Photo Flash	-20~+55°C	●				330WV(350SV)	60~180	76
	AF-NP	04	音频设备用无极性品 Non-Polarized ,For Audio Equipment	-40~+85°C (105°C)	●		●		50 (100)	1.0 ~ 100	77
	BP	04	无极性品 Non- Polarized	-40~+105°C	●				6.3~100	0.47~4700	※
	LL	04	低漏电流品 Low Leakage Current	-40~+105°C	●				6.3~50	0.1~4700	※
	BW	02	轴向引出标准品 Axial Lead Type	-40~+85°C (105°C)	●					1.0 ~ 100	※

大型铝电解电容器 LARGE CAN ALUMINIUM ELECTROLYTIC CAPACITORS

用途区分 Classification	系列 Series	JIS Configuration	概要 Applications	温度范围 Operating Temperature (°C)	特性Features				额定电压范围 Rated W. V (V. DC)	额定静电容量 范围 Capacitance (μF)	页码 Page
					标准品 Standard type	小型化品 Smaller-sized & low profile	低阻抗品 Low impedance	长寿命品 Long life			
大型焊针品 Snap-in Type Electrolytic Capacitors	SC	69	焊针式85°C标准品 Snap-in Type, Standard	-40(-25)~+85°C	●	●			10~450	56~82000	80
	HS	69	焊针式105°C标准品 Snap-in Type, Wide Temperature Range	-40(-25)~+105°C	●	●			10~450	47~68000	84
	HL	69	焊针式105°C长寿命品 Snap-in Type, Wide Temperature Long Life	-40(-25)~+105°C			●	●	10~500	47~56000	88
	YFX	69	焊针式105°C 20mm高品 Snap-in Type, 20mm High, Wide Temperature			●	●		10~450	39~10000	91
	AP	69	焊针式过电压品 Snap-in Type, Withstanding Overvoltage				●	●	200~400	22~1500	93
	DQ		焊针式横置型品 Snap-in Type, Exhaust Type			●	●		200~400	68~1200	※
	HK	69 NEW	高温品、小型化品 Snap-in Type, High Ripple, Miniaturized	-25~+105°C			●	●	400~450	56~680	95
大型螺栓/焊片式产品 Screw Terminal Type/Lug Type Electrolytic Capacitors	STC	33	螺栓式85°C标准品 Screw Terminal Type, Standard	-40(-25)~+85°C	●	●	●		10~450	270~680000	99
	HTC	33	螺栓式105°C标准品 Screw Terminal Type, Wide Temperature Range	-40(-25)~+105°C	●		●		10~400	220~680000	101
	LTC	33	螺栓式105°C长寿命品 Screw Terminal Type, Long Life	-40(-25)~+105°C			●	●	350~450	1000~18000	103
特殊品 Special type	AUDIO	69/62	焊针或焊片式音响设备专用品 Snap-in /Lug Terminal Type For Audio Equipment	-40~+85°C	●		●		35~125	2200~33000	104
	GK		变频空调专用品 For Inverter And Air-conditioner	-25~+85°C (105°C)			●	●	400~450	330~3300	108
闪光灯用 Photo Flash Used	FHK		接头端子型闪光灯用主电容器 Electrolytic capacitors for photoflash applications with Lug terminal	-20~+55°C			●	●	330/360	150~1500	111
	FCD	NEW	急速发光闪光灯用主电容器 Electrolytic capacitors for rapid strobe flash applications	-25~+85°C (105°C)			●	●	360~450	40~400	112